NSN 5905-01-282-8942

Film Fixed Resistor Network - Page 1 of 2



Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -100.0/+100.0 Electrical Resistance: -4.750 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.1 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.368 inches and 0.998 inches Body Width: Between 0.368 inches and 0.103 inches Body Height: Between 0.321 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating in Watts: 1.800 total network End Application:
Electrical Resistance: 4.750 kilohms Resistance Tolerance in Percent: -1.0004+.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -85.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Eletween 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Width: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating in Watts: 1.800 total network
4.750 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Quantity: 10 Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.096 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating in Watts: 1.800 total network
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.032 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating in Watts: 1.800 total network
-1,000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Length: Between 0.050 inches and 0.032 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating in Watts: 1.800 total network
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.322 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.950 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.322 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.322 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Body Length: Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Between 0.968 inches and 0.998 inches Body Width: Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Between 0.050 inches and 0.103 inches Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Body Height: Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Between 0.332 inches and 0.352 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.800 total network
Ladder network Power Dissipation Rating In Watts: 1.800 total network
Power Dissipation Rating In Watts: 1.800 total network
1.800 total network
End Application:
C130anaaq17fl
Identical Value Resistor Quantity:
9 each resistor
Unpackaged Unit Weight:
1.7 grams
Style Designator:
Single inline
Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-282-8942

Film Fixed Resistor Network - Page 2 of 2



Sı	pecif	icati	on Da	ta:
----	-------	-------	-------	-----

81349-mil-r-83401/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0