## NSN 5905-01-283-0591

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-283-0591

view Orillite at https://aerobasegroup.com/nsn/3903-01-203-0091
Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Terminal Length:
Between 0.580 inches and 0.624 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
Between 0.360 inches and 0.390 inches
Body Length:
0.500 inches
Body Width:
Between 0.610 inches and 0.640 inches
Body Height:
Between 0.610 inches and 0.640 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.100 inches
End Application:
6625-01-251-4775
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 megohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

## NSN 5905-01-283-0591

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No