Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-286-2798

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 1.000 inches and 1.094 inches Shaft Diameter: 0.125 inches Shaft Length: Between 0.578 inches and 0.672 inches **Mounting Bushing Length:** Between 0.219 inches and 0.297 inches **Body Length:** Between 1.000 inches and 1.126 inches Shaft Style: Round, slotted Shaft Bearing Type: Sleeve Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.235 inches and 0.265 inches **End Application:** An/mpn-14k mo Screw Thread Diameter: 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Rear end



Mounting Method: Standard bushing **Features Provided:** Humidity proof **Cubic Measure:** 1.058 cubic inches **Electrical Resistance Per Section:** 75.0 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 290.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 6.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-22/2 government specification Shelf Life: Unit Of Measure: **Demilitarization:** A002a0

N/a

No Fiig: