NSN 5905-01-286-5150

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-286-5150 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** 0.172 inches **Body Length:** 0.250 inches **Body Width:** Between 0.230 inches and 0.270 inches **Body Height:** Between 0.230 inches and 0.270 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 215.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 4.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Fragility Factor:** Moderately rugged **End Application:** An/mpn-14k mo **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof

Cubic Measure:

0.016 cubic inches

NSN 5905-01-286-5150

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Flectrical	Resistance	Per Section:
Liccuitai	Nesisiance	i ei oechon.

25.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

240.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.095 mils and 0.105 centimeters

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/4 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0