NSN 5905-01-287-4278

Film Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-287-4278 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -100.0/+100.0 |
| Electrical Resistance: |
| 270.000 ohms |
| Resistance Tolerance In Percent: |
| -2.000/+2.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 8 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.100 inches and 0.150 inches |
| Body Length: |
| Between 0.768 inches and 0.784 inches |
| Body Width: |
| Between 0.070 inches and 0.090 inches |
| Body Height: |
| Between 0.232 inches and 0.250 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 1.100 total network |
| End Application: |
| 4920-01-187-4068 automatic radar test system |
| Identical Value Resistor Quantity: |
| 7 each resistor |
| Unpackaged Unit Weight: |
| 1.5 grams |
| Style Designator: |
| Single inline |
| Shelf Life: |

N/a

NSN 5905-01-287-4278

Film Fixed Resistor Network - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A001a0