

View Online at <https://aerobasegroup.com/nsn/5905-01-287-6601>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.7495 inches and 0.7500 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Undercut Diameter:**

0.906 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

1.062 centimeters

**Shaft Diameter:**

Between 0.1245 inches and 0.1250 inches

**Shaft Length:**

Between 0.594 inches and 0.656 inches

**Body Length:**

0.810 inches

**Mounting Lip Diameter:**

0.9060 inches

**Mounting Lip Depth:**

0.0570 mils and 0.0670 centimeters

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

360.0

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

0.40 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.001 inches

**Mechanical Backlash In Deg Angular Rotation:**

0.5

**Fragility Factor:**

Moderately rugged

**End Application:**

Lantirnavpod

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.492 cubic inches

**Electrical Resistance Per Section:**

10.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Function Characteristic Per Section:**

7 oclock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Test Data Document:**

81349-mil-r-39023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0