Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-287-7513

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
Between 0.859 inches and 0.891 inches
Mounting Bushing Length:
0.500 inches
Body Length:
Between 0.563 inches and 0.625 inches
Body Width:
Between 0.609 inches and 0.641 inches
Body Height:
Between 0.609 inches and 0.641 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Dual concentric
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.359 inches and 0.391 inches
Fragility Factor:
Moderately rugged
End Application:
5865-01-236-4235 mobile electron
Screw Thread Diameter:
Batwaan 0.350 inchas and 0.301 inchas

Between 0.359 inches and 0.391 inches

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Center To Center Distance Between Terminal Rows:

Between 0.080 inches and 0.090 inches

Features Provided:

Humidity proof

Cubic Measure:

0.232 cubic inches

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0