NSN 5905-01-289-7337

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-289-7337

Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established
Electrical Resistance: 2.000 kilohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.988 inches and 0.998 inches
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
-2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
-55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Inclosure Method: Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Encapsulated Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Terminal Quantity: 10 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Pin Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Terminal Length: Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Between 0.125 inches and 0.150 inches Body Length: Between 0.968 inches and 0.998 inches
Body Length: Between 0.968 inches and 0.998 inches
Between 0.968 inches and 0.998 inches
Between 0.050 inches and 0.103 inches
Body Height:
Between 0.332 inches and 0.352 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
1.800 total network
End Application:
Lantirn mob s
Identical Value Resistor Quantity:
9 each resistor
Unpackaged Unit Weight:
1.7 grams
Style Designator:
Single inline
Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-289-7337

Film Fixed Resistor Network - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-r-83401/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0