NSN 5905-01-290-7704

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-290-7704 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.200 inches **Shaft Diameter:** 0.090 inches **Shaft Length:** 0.060 inches **Body Length:** 0.395 inches **Body Width:** 0.240 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Moderately rugged **End Application:** F16aircombfit **Terminal Location:** Rear end **Mounting Method:** Clamp ring

Features Provided:

Humidity proof

NSN 5905-01-290-7704

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Cubic Measure:
0.036 cubic inches
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Unpackaged Unit Weight:
0.98 grams
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0