NSN 5905-01-291-0672

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-291-0672

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
Between 0.360 inches and 0.390 inches
Body Length:
Between 0.610 inches and 0.640 inches
Body Width:
Between 0.610 inches and 0.640 inches
Body Height:
Between 0.610 inches and 0.640 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 234.0 and 246.0
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.185 inches and 0.215 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0

32.0

NSN 5905-01-291-0672

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Center To Center Distance Between Terminal Rows:
Between 0.185 inches and 0.215 inches
Cubic Measure:
0.244 cubic inches
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.185 mils and 0.215 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
V single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0