

View Online at <https://aerobasegroup.com/nsn/5905-01-291-0674>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.734 inches

First Flat Length:

0.344 inches

Flat Height:

0.094 inches

Body Diameter:

0.484 mils and 0.516 centimeters

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.672 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Maximum Starting Torque:

13.00 inch-ounces

Maximum Running Torque:

13.00 inch-ounces

Maximum Stop Torque:

32.00 inch-ounces

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

Between 0.240 inches and 0.250 inches

Mechanical Backlash In Deg Angular Rotation:

3.0

Fragility Factor:

Moderately rugged

End Application:

Md-xxx/usq-83

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Panel seal

Cubic Measure:

0.134 cubic inches

Electrical Resistance Per Section:

100.0 percent, rated amperes c and better

Rotary Actuator Travel In Angular Deg:

Between 290.0 and 300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary at 10'30 oclock

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0