NSN 5905-01-291-0676

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Not established **Body Diameter:**

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-291-0676

•
0.860 mils and 0.890 centimeters
Shaft Diameter:
Between 0.235 inches and 0.245 inches
Shaft Length:
Between 0.781 inches and 0.843 inches
Mounting Bushing Length:
Between 0.297 inches and 0.327 inches
Body Length:
Between 0.735 inches and 0.765 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3610.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Maximum Stop Torque:
75.00 inch-ounces
Nonturn Device Location:
At 3 oclock and at 9 oclock and at 12 oclock
Nonturn Device Radius:
0.438 inches
Fragility Factor:
Moderately rugged
End Application:
6625-01-170-6878 oscilloscope
Screw Thread Diameter:
Between 0.370 inches and 0.380 inches
Screw Thread Series Designator:
Unef

NSN 5905-01-291-0676

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.476 cubic inches
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0