

View Online at <https://aerobasegroup.com/nsn/5905-01-291-2842>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**First Flat Length:**

0.500 inches

**Flat Height:**

Between 0.215 inches and 0.220 inches

**Body Diameter:**

1.000 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.812 inches

**Shaft Style:**

Round, flatted

**Shaft Bearing Type:**

Sleeve

**Switch Type:**

Rotary

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.438 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

6625-01-125-3469 sweep generator

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Standard Taper Curve Per Section:**

V single section

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0