NSN 5905-01-291-4935

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-291-4935

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
100.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
10
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.968 inches and 0.998 inches
Body Width:
Between 0.050 inches and 0.103 inches
Body Height:
Between 0.332 inches and 0.352 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
1.800 total network
End Application:
Seq logic cir
Identical Value Resistor Quantity:
9 each resistor
Unpackaged Unit Weight:
1.7 grams
Style Designator:
Single inline
Test Data Document:
04040 million 00404 million frankritar frankritar kan kullatiar, kan kullatiar kun kun kullatiar kun kun kullatiar kun kun kullatiar kun

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-291-4935

Film Fixed Resistor Network - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-r-83401/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0