NSN 5905-01-292-5852

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-292-5852
Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
33.52 millimeters
Mounting Bushing Length:
11.93 millimeters
Body Length:
22.35 millimeters
Shaft Style:
Round
Switch Type:
Rotary
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
202.5
Switch Operating Position:
End of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
End Application:
3810-00-018-2021; crane, truck mounted
Screw Thread Diameter:
0.438 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
28.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
3.0 ohms c and better finish

NSN 5905-01-292-5852

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
270.0
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 1st section
Actuator Travel Control Feature:
Stops
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0