NSN 5905-01-293-1313

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-293-1313

Section Quantity: 1 Body Style: Rectangular Reliability Indicator: Not established Terminal Length: 0.187 inches Shaft Diameter: 0.078 inches		
Body Style: Rectangular Reliability Indicator: Not established Terminal Length: 0.187 inches Shaft Diameter:		
Rectangular Reliability Indicator: Not established Terminal Length: 0.187 inches Shaft Diameter:		
Reliability Indicator: Not established Terminal Length: 0.187 inches Shaft Diameter:		
Not established Terminal Length: 0.187 inches Shaft Diameter:		
Terminal Length: 0.187 inches Shaft Diameter:		
0.187 inches Shaft Diameter:		
Shaft Diameter:		
0.078 inches		
Shaft Length:		
0.040 inches		
Body Length:		
0.312 inches		
Body Width:		
0.190 inches		
Body Height:		
0.312 inches		
Shaft Style:		
Round, slotted		
Actuator Type:		
Single shaft		
Center To Center Distance Between Terminals:		
0.200 inches		
Terminal Location:		
Lower adjacent side two rows		
Mounting Method:		
Terminal		
Center To Center Distance Between Terminal Rows:		
0.100 inches		
Electrical Resistance Per Section:		
2.0 kilohms single section		
Center To Center Distance Between Center Terminal And Outside Terminal:		
0.100 inches		
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:		
150.0 single section		
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:		
-50.0/+50.0 single section		
Power Dissipation Rating Per Section In Watts:		
0.6 free air single section		
Resistance Tolerance Per Section In Percent:		

-5.0/+5.0 single section

NSN 5905-01-293-1313

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg	Celsius Per Section	At Full Rated Power:
----------------------------	---------------------	----------------------

70.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0