

View Online at <https://aerobasegroup.com/nsn/5905-01-293-2392>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0730 inches

Body Diameter:

2.031 inches

Shaft Diameter:

Between 0.2494 inches and 0.250 inches

Shaft Length:

Between 0.719 inches and 0.781 inches

Body Length:

1.312 inches

Mounting Lip Diameter:

Between 1.9900 inches and 2.0050 inches

Mounting Lip Depth:

Between 0.0870 inches and 0.0970 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 348.0 and 352.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.002 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Cubic Measure:

4.122 cubic inches

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Unpackaged Unit Weight:

114.0 grams

Test Data Document:

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-12934 specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0