NSN 5905-01-293-4220

Hybrid Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-293-4220

Section Quantity:
1
Body Style: Rectangular
Terminal Length:
0.300 inches
Body Length:
0.375 inches
Body Width:
0.150 inches
Body Height:
0.375 inches
Actuator Type:
Slider
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.100 inches
Mounting Facility Quantity:
2
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
2.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:

Continuous motion and stops and clutch

NSN 5905-01-293-4220

Hybrid Variable Resistor - Page 2 of 2

Per Section At Full Rated Power:



Ambient Tempurature In Deg Celsius
85.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Multiturn cermet trimmer; 0.375 in. Sq
Terminal Type And Quantity:
3 screw and 3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A002a0