Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-293-5024

### Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

#### **Terminal Length:**

0.160 inches

#### Shaft Diameter:

0.080 inches

Shaft Length:

0.040 inches

Body Length:

0.312 inches

#### Body Width:

0.190 inches

## Body Height:

0.312 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

3.00 inch-ounces

#### Maximum Running Torque:

3.00 inch-ounces

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Electrical Resistance Per Section:**

1.0 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section



**Power Dissipation Rating Per Section In Watts:** 0.3 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 pin Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0