## NSN 5905-01-294-7105

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-294-7105

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side single row
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## NSN 5905-01-294-7105

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0