

View Online at <https://aerobasegroup.com/nsn/5905-01-295-3321>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.580 inches and 0.624 inches

**Shaft Diameter:**

Between 0.245 inches and 0.255 inches

**Shaft Length:**

Between 0.870 inches and 0.880 inches

**Mounting Bushing Length:**

Between 0.360 inches and 0.390 inches

**Body Length:**

Between 0.883 inches and 0.917 inches

**Body Width:**

Between 0.610 inches and 0.640 inches

**Body Height:**

Between 0.610 inches and 0.640 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 235.0 and 245.0

**Maximum Starting Torque:**

1.50 inch-ounces

**Maximum Running Torque:**

1.50 inch-ounces

**Maximum Stop Torque:**

64.00 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.195 inches and 0.205 inches

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

Between 0.370 inches and 0.380 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.376 cubic inches

**Electrical Resistance Per Section:**

10.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

Between 295.0 and 305.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.095 mils and 0.105 centimeters

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0