Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-295-3323

## Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.058 inches and 0.098 inches Shaft Length: Between 0.025 inches and 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.490 inches and 0.510 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 7200.0 Lateral Distance Between Mounting Hole Centers: Between 0.517 inches and 0.526 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 20.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 16200.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# NSN 5905-01-295-3323

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



#### **Actuator Travel Control Feature:**

Continuous motion

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

#### **Test Data Document:**

81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 wire lead

**Specification Data:** 

81349-mil-r-27208/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A002a0