

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5905-01-297-9816
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
0.250 inches
Body Length:
0.180 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
215.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Maximum Stop Torque:
6.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.125 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
25.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Special Features:

Sealed to permit cleaning in common solvents



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0