NSN 5905-01-298-1169

Section Quantity:

120.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-298-1169

1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
1.000 inches
Body Length:
0.276 inches
Body Width:
0.287 inches
Body Height:
0.339 inches
Shaft Bearing Type:
Sleeve
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.185 inches and 0.215 inches
Fragility Factor:
Moderately rugged
End Application:
6625-01-159-3106oscilloscope
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Features Provided:
Humidity proof
Cubic Measure:
0.027 cubic inches
Electrical Resistance Per Section:
1.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-01-298-1169

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: