## NSN 5905-01-298-4327

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-298-4327

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -20.0/+20.0  |
| Electrical Resistance:   |
| 470.000 ohms   |
| Resistance Tolerance In Percent:   |
| -0.100/+0.100  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+275.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.001  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| Between 0.156 inches and 0.218 inches  |
| Body Length:   |
| Between 0.498 inches and 0.622 inches  |
| Power Dissipation Rating In Watts:   |
| 3.000 free air   |
| End Application:   |
| 1520-01-088-3669 helicopter, cargo-transport   |
| Cubic Measure (non-core):  |
| 0.023 cubic inches   |
| Unpackaged Unit Weight:  |
| 4.0 grams  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39007/11 government specification  |

N/a

Shelf Life:

## NSN 5905-01-298-4327

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A001a0