# NSN 5905-01-298-5909

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-298-5909

Section Quantity:	
1	
Body Style:	
Rectangular w/mounting holes/slots	
Reliability Indicator:	
Established	
Reliability Failure Rate Level In Percent:	
0.010	
Terminal Length:	
Between 0.469 inches and 0.531 inches	
Mounting Hole Diameter:	
0.088 mils and 0.098 centimeters	
Shaft Diameter:	
Between 0.100 inches and 0.130 inches	
Shaft Length:	
Between 0.036 inches and 0.080 inches	
Body Length:	
Between 1.240 inches and 1.260 inches	
Body Width:	
Between 0.180 inches and 0.200 inches	
Body Height:	
Between 0.300 inches and 0.330 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Center To Center Distance Between Terminals:	
Between 0.690 inches and 0.710 inches	
Lateral Distance Between Mounting Hole Centers:	
Between 0.995 inches and 1.005 inches	
Mounting Facility Quantity:	
2	
Terminal Location:	
Lower adjacent side two rows	
Mounting Method:	
Unthreaded hole	
Center To Center Distance Between Terminal Rows:	
Between 0.090 inches and 0.110 inches	
Cubic Measure:	
0.075 cubic inches	
Electrical Resistance Per Section:	

200.0 ohms c and better flooring

# NSN 5905-01-298-5909

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center	Terminal And Outside Terminal:
--	--------------------------------

0.290 mils and 0.310 centimeters

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

## **Test Data Document:**

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 pin

#### **Specification Data:**

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A002a0