Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-298-5909

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** Between 0.469 inches and 0.531 inches Mounting Hole Diameter: 0.088 mils and 0.098 centimeters Shaft Diameter: Between 0.100 inches and 0.130 inches Shaft Length: Between 0.036 inches and 0.080 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.300 inches and 0.330 inches Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

Between 0.690 inches and 0.710 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Mounting Facility Quantity:

2

Terminal Location: Lower adjacent side two rows **Mounting Method:** Unthreaded hole **Center To Center Distance Between Terminal Rows:** Between 0.090 inches and 0.110 inches **Cubic Measure:** 0.075 cubic inches **Electrical Resistance Per Section:**

200.0 ohms c and better flooring



Center To Center Distance Between Center Terminal And Outside Terminal:

0.290 mils and 0.310 centimeters

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0