NSN 5905-01-299-5278

-50.0/+50.0

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-299-5278

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

| Electrical Resistance: | | | | |
|--|--|--|--|--|
| 1.200 kilohms | | | | |
| Resistance Tolerance In Percent: | | | | |
| -1.000/+1.000 | | | | |
| Ambient Tempurature In Deg Celsius At Full Rated Power: | | | | |
| 25.0 | | | | |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: | | | | |
| 275.0 | | | | |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: | | | | |
| -55.0/+275.0 | | | | |
| Inclosure Method: | | | | |
| Encased | | | | |
| Terminal Type: | | | | |
| Tab, solder lug | | | | |
| Reliability Indicator: | | | | |
| Not established | | | | |
| Terminal Length: | | | | |
| 0.266 inches | | | | |
| Body Length: | | | | |
| 0.600 inches | | | | |
| Body Width: | | | | |
| 0.334 inches | | | | |
| Body Height: | | | | |
| 0.320 inches | | | | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | | | | |
| 0.444 inches | | | | |
| Power Dissipation Rating In Watts: | | | | |
| 3.000 free air | | | | |
| Mounting Hole Size: | | | | |
| 0.093 inches | | | | |
| Style Designator: | | | | |
| Axial terminal (s) | | | | |
| Test Data Document: | | | | |
| 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification | | | | |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain | | | | |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | | | | |
| Specification Data: | | | | |
| 81349-mil-r-18546/1 government specification | | | | |
| Shelf Life: | | | | |
| N/a | | | | |
| Unit Of Measure: | | | | |

NSN 5905-01-299-5278

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| | tariz | |
|--|-------|--|
| | | |
| | | |

No

Fiig:

A001a0