## NSN 5905-01-299-6248

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-299-6248

Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
Between 0.470 inches and 0.530 inches
Shaft Diameter:
Between 0.100 inches and 0.130 inches
Shaft Length:
Between 0.036 inches and 0.080 inches
Body Length:
Between 1.240 inches and 1.260 inches
Body Width:
Between 0.180 inches and 0.200 inches
Body Height:
Between 0.300 inches and 0.330 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Effective Electrical Rotation in Deg Angular Rotation.
7920.0
7920.0
7920.0  Maximum Starting Torque:
7920.0  Maximum Starting Torque: 5.00 inch-ounces
7920.0  Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque:
7920.0  Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque: 5.00 inch-ounces
7920.0  Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque: 5.00 inch-ounces  Center To Center Distance Between Terminals:
7920.0  Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque: 5.00 inch-ounces  Center To Center Distance Between Terminals:  Between 0.690 inches and 0.710 inches
7920.0  Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque: 5.00 inch-ounces  Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches  Fragility Factor:
7920.0  Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque: 5.00 inch-ounces  Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches  Fragility Factor:  Moderately rugged
Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches Fragility Factor: Moderately rugged End Application:
Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches Fragility Factor: Moderately rugged End Application: 4920-01-083-0429 stand, test
Maximum Starting Torque: 5.00 inch-ounces  Maximum Running Torque: 5.00 inch-ounces  Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches  Fragility Factor: Moderately rugged  End Application: 4920-01-083-0429 stand, test  Lateral Distance Between Mounting Hole Centers:
Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches Fragility Factor: Moderately rugged End Application: 4920-01-083-0429 stand, test Lateral Distance Between Mounting Hole Centers: Between 0.990 inches and 1.010 inches
Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches Fragility Factor: Moderately rugged End Application: 4920-01-083-0429 stand, test Lateral Distance Between Mounting Hole Centers: Between 0.990 inches and 1.010 inches Terminal Location:
Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches Fragility Factor: Moderately rugged End Application: 4920-01-083-0429 stand, test Lateral Distance Between Mounting Hole Centers: Between 0.990 inches and 1.010 inches Terminal Location: Lower adjacent side two rows
Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: Between 0.690 inches and 0.710 inches Fragility Factor: Moderately rugged End Application: 4920-01-083-0429 stand, test Lateral Distance Between Mounting Hole Centers: Between 0.990 inches and 1.010 inches Terminal Location: Lower adjacent side two rows Mounting Method:

## NSN 5905-01-299-6248

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Cubic Measure:
0.083 cubic inches
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.290 mils and 0.310 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0