

View Online at <https://aerobasegroup.com/nsn/5905-01-300-5810>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

Between 0.183 inches and 0.213 inches

Shaft Diameter:

Between 0.160 inches and 0.180 inches

Shaft Length:

Between 0.030 inches and 0.050 inches

Body Length:

Between 0.230 inches and 0.270 inches

Body Width:

Between 0.155 inches and 0.185 inches

Body Height:

Between 0.250 inches and 0.290 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

4320.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.180 inches and 0.220 inches

Fragility Factor:

Moderately rugged

End Application:

F/tf-15a acft

Terminal Location:

Rear end

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.014 cubic inches

Electrical Resistance Per Section:

5.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

4320.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.090 mils and 0.110 centimeters

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0