

View Online at <https://aerobasegroup.com/nsn/5905-01-300-5815>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.183 inches and 0.213 inches

**Shaft Diameter:**

Between 0.160 inches and 0.180 inches

**Shaft Length:**

Between 0.030 inches and 0.050 inches

**Body Length:**

Between 0.230 inches and 0.270 inches

**Body Width:**

Between 0.155 inches and 0.185 inches

**Body Height:**

Between 0.250 inches and 0.290 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

4320.0

**Maximum Starting Torque:**

3.00 inch-ounces

**Maximum Running Torque:**

3.00 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.180 inches and 0.220 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

F/15a acft

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

Between 0.090 inches and 0.110 inches

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.014 cubic inches

**Electrical Resistance Per Section:**

20.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

4320.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.090 mils and 0.110 centimeters

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0