## NSN 5905-01-300-7686

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-300-7686

<b>Tempurature</b>	Coefficient	Of Resistance	In Ppm	Per Deg	Celsius:
--------------------	-------------	---------------	--------	---------	----------

-50.0 to 50.0

**Electrical Resistance:** 

85.000 ohms

**Resistance Tolerance In Percent:** 

-0.100 to 0.100

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 175.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.001

**Terminal Length:** 

Between 1.000 inches and 1.625 inches

**Body Diameter:** 

Between 0.160 inches and 0.328 inches

**Body Length:** 

Between 0.500 inches and 0.875 inches

**Power Dissipation Rating In Watts:** 

0.500 free air

**End Application:** 

4935-00-106-9734 supplementary equipment, guided missile system test station

**Unpackaged Unit Weight:** 

1.6 grams

**Style Designator:** 

Axial terminal each end

**Test Data Document:** 

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-r-55182/6 government specification

Shelf Life:

N/a

## NSN 5905-01-300-7686

Film Fixed Resistor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A001a0