NSN 5905-01-300-8268

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-300-8268 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3120 inches and 1.3125 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.285 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.600 inches and 0.640 inches **Body Length:** 1.510 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Fragility Factor:**

Moderately rugged **End Application:** Panel, control

NSN 5905-01-300-8268

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
2.448 cubic inches
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
75.0 single section
Test Data Document:
03956-1803993 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0