Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-300-8893

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
0.300 inches
Shaft Diameter:
Between 0.050 inches and 0.100 inches
Shaft Length:
0.080 inches
Body Length:
0.420 inches
Body Width:
Between 0.145 inches and 0.195 inches
Body Height:
Between 0.360 inches and 0.390 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 5400.0 and 10800.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
End Application:
1055-01-251-9756 rocket-launcher
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal



Features Provided: Humidity proof **Cubic Measure:** 0.027 cubic inches **Electrical Resistance Per Section:** 10.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-39035/2 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0