Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-301-4794

## Electrical Resistance:

0.499 ohms

**Resistance Tolerance In Percent:** 

-0.100/+0.100

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

## 275.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.001

**Terminal Length:** 

1.500 inches

Body Diameter:

Between 0.281 inches and 0.343 inches

**Body Length:** 

Between 0.813 inches and 0.937 inches

**Power Dissipation Rating In Watts:** 

5.000 free air

Cubic Measure (non-core):

0.087 cubic inches

**Special Features:** 

Temp coef not to exceed plus 650 ppm

**Unpackaged Unit Weight:** 

5.0 grams

Style Designator:

Axial terminal each end

## Test Data Document:

81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39007/6 government specification

Shelf Life:

N/a



Demilitarization:

No

Fiig:

A001a0