NSN 5905-01-301-5509

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-301-5509

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.560 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.344 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.380 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
25.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section

-10.0/+10.0 single section

Resistance Tolerance Per Section In Percent:

NSN 5905-01-301-5509

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0