NSN 5905-01-301-9712

Inductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-301-9712 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -50.0/+50.0 |
| Electrical Resistance: |
| 3.010 ohms |
| Resistance Tolerance In Percent: |
| -0.500/+0.500 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| -55.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+275.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.638 inches and 0.762 inches |
| Body Diameter: |
| Between 1.157 inches and 1.219 inches |
| Mounting Bushing Length: |
| Between 0.594 inches and 0.656 inches |
| Body Length: |
| Between 1.644 inches and 1.706 inches |
| Power Dissipation Rating In Watts: |
| 50.000 free air |
| Mounting Bushing Diameter: |
| Between 0.844 inches and 0.906 inches |
| End Application: |
| Id panel |
| Unpackaged Unit Weight: |
| 80.0 grams |
| Style Designator: |
| Axial terminals one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |

No

NSN 5905-01-301-9712

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0