Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-302-0409

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

200.000 kilohms

**Resistance Tolerance In Percent:** 

-2.000/+2.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

### Terminal Quantity:

16

#### Terminal Type:

Tab, solder lug

# Reliability Indicator:

Not established

## Terminal Length:

Between 0.145 inches and 0.215 inches

## **Body Length:**

Between 0.784 inches and 0.876 inches

#### **Body Width:**

Between 0.240 inches and 0.305 inches

#### **Body Height:**

0.180 inches

## Schematic Diagram Designator:

Isolated array

#### Power Dissipation Rating In Watts:

1.600 total network

## Terminal Width:

Between 0.015 inches and 0.022 inches

#### End Application:

Spa-25g 105

## Identical Value Resistor Quantity:

8 each resistor

## Unpackaged Unit Weight:

1.5 grams

## Style Designator:

Dual inline

Film Fixed Resistor Network - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0