## NSN 5905-01-302-2784

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-302-2784
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0/+50.0
Electrical Resistance:
4.020 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.407 inches and 0.469 inches
Body Diameter:
Between 0.844 inches and 0.906 inches
Mounting Bushing Length:
Between 0.515 inches and 0.577 inches
Body Length:
Between 0.781 inches and 0.843 inches
Power Dissipation Rating In Watts:
25.000 free air
Mounting Bushing Diameter:
Between 0.594 inches and 0.656 inches
End Application:
Id panel
Cubic Measure (non-core):
1.199 cubic inches
Unpackaged Unit Weight:
22.0 grams
Style Designator:
Axial terminals one end
Test Data Document:
26512-gr815ec drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

N/a

Shelf Life:

## NSN 5905-01-302-2784

Inductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0