NSN 5905-01-302-3267

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-302-3267
Section Quantity:
2
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.922 inches and 1.016 inches
Body Width:
Between 0.609 inches and 0.641 inches
Body Height:
Between 0.609 inches and 0.641 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.515 inches and 0.547 inches
Fragility Factor:
Moderately rugged
End Application:
Panel, control
Screw Thread Diameter:

0.375 inches

NSN 5905-01-302-3267

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
_ower adjacent side two rows
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.417 cubic inches
Electrical Resistance Per Section:
2.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
5.5/+5.5 -55 degrees celsius all sections and -3.0/+3.0 -25 degrees celsius all sections and -1.5/+1.5 0 degrees celsius all sections and
3.0/+3.0 85 degrees celsius all sections and -5.0/+5.0 120 degrees celsius all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0