NSN 5905-01-302-8932

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-302-8932 **Section Quantity:** 3 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** Between 0.359 inches and 0.391 inches **Body Length:** Between 1.297 inches and 1.391 inches **Body Width:** Between 0.609 inches and 0.641 inches **Body Height:** Between 0.609 inches and 0.641 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.515 inches and 0.547 inches **Fragility Factor:** Moderately rugged **End Application:** Panel, indicat **Screw Thread Diameter:**

0.375 inches

NSN 5905-01-302-8932

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Ferminal Location:
_ower adjacent side two rows
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.572 cubic inches
Electrical Resistance Per Section:
2.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
5.5/+5.5 -55 degrees celsius all sections and -3.0/+3.0 -25 degrees celsius all sections and -1.5/+1.5 0 degrees celsius all sections and
3.0/+3.0 85 degrees celsius all sections and -5.0/+5.0 120 degrees celsius all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0