NSN 5905-01-302-8936

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-302-8936 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.859 mils and 0.891 centimeters **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** Between 0.656 inches and 0.708 inches **Mounting Bushing Length:** Between 0.296 inches and 0.328 inches **Body Length:** Between 1.448 inches and 1.466 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 3610.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.003 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 0.003 inches

Fragility Factor:
Moderately rugged

NSN 5905-01-302-8936

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Cubic Measure:
0.914 cubic inches
Electrical Resistance Per Section:
390.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.075/+0.075 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0