NSN 5905-01-303-4778

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-303-4778			
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:			
-100.0/+100.0			
Electrical Resistance:			
100.000 ohms			
Resistance Tolerance In Percent:			
-2.000/+2.000			
Ambient Tempurature In Deg Celsius At Full Rated Power:			
70.0			
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:			
125.0			
Tempurature Range Of Tempurature Coefficient In Deg Celsius:			
-55.0/+125.0			
Inclosure Method:			
Encapsulated			
Terminal Quantity:			
8			
Terminal Type:			
Pin			
Reliability Indicator:			
Not established			
Terminal Length:			
Between 0.125 inches and 0.150 inches			
Body Length:			
Between 0.768 inches and 0.798 inches			
Body Width:			
Between 0.050 inches and 0.103 inches			
Body Height:			
Between 0.177 inches and 0.197 inches			
Schematic Diagram Designator:			
Ladder network			
Power Dissipation Rating In Watts:			
0.840 total network			
End Application:			
C t 2 m-m rad			
Identical Value Resistor Quantity:			
7 each resistor			
Special Features:			
Nuclear hardness critical items			
Nuclear Hardness Critical Feature:			
Hardened			

1.5 grams

Unpackaged Unit Weight:

NSN 5905-01-303-4778

Film Fixed Resistor Network - Page 2 of 2



04	D!-	
Stvie	Desig	nator:

Single inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0