NSN 5905-01-303-4778

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-303-4778				
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-100.0/+100.0				
Electrical Resistance:				
100.000 ohms				
Resistance Tolerance In Percent:				
-2.000/+2.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
70.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
125.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+125.0				
Inclosure Method:				
Encapsulated				
Terminal Quantity:				
8				
Terminal Type:				
Pin				
Reliability Indicator:				
Not established				
Terminal Length:				
Between 0.125 inches and 0.150 inches				
Body Length:				
Between 0.768 inches and 0.798 inches				
Body Width:				
Between 0.050 inches and 0.103 inches				
Body Height:				
Between 0.177 inches and 0.197 inches				
Schematic Diagram Designator:				
Ladder network				
Power Dissipation Rating In Watts:				
0.840 total network				
End Application:				
C t 2 m-m rad				
Identical Value Resistor Quantity:				
7 each resistor				
Special Features:				
Nuclear hardness critical items				
Nuclear Hardness Critical Feature:				
Hardened				

1.5 grams

Unpackaged Unit Weight:

NSN 5905-01-303-4778

Film Fixed Resistor Network - Page 2 of 2



041	- D-	-:	4
Stvi	e ve	sıar	ator:

Single inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0