## NSN 5905-01-305-5177

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-305-5177 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.971 inches and 1.065 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.375 inches **Fragility Factor:** Moderately rugged **End Application:** 

Ultrasonic fl
Screw Thread Diameter:
0.250 inches

## NSN 5905-01-305-5177

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.416 cubic inches
Electrical Resistance Per Section:
500.0 ohms all sections
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+4.5 -55 degrees celsius all sections and +0.0/+2.5 -25 degrees celsius all sections and +0.0/+1.5 0 degrees celsius all sections and
-1.5/+1.5 85 degrees celsius all sections and +0.0/+3.5 120 degrees celsius all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Specification Data:
30003-1642as706-1 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiia: