NSN 5905-01-306-1159

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-306-1159 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** Between 0.180 inches and 0.200 inches **Body Width:** Between 0.360 inches and 0.390 inches **Body Height:** Between 0.360 inches and 0.390 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Fragility Factor:** Moderately rugged **End Application:** 6625-01-255-4547 voltmeter **Terminal Location:** Rear end **Mounting Method: Terminal Cubic Measure:** 0.030 cubic inches **Electrical Resistance Per Section:** 10.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts: Resistance Tolerance Per Section In Percent:**

0.5 7th secondary quality -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops

NSN 5905-01-306-1159

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Immersion sealed
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No