

View Online at <https://aerobasegroup.com/nsn/5905-01-306-8731>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.860 inches and 0.890 inches

**Shaft Diameter:**

Between 0.249 inches and 0.250 inches

**Shaft Length:**

Between 0.781 inches and 0.843 inches

**Mounting Bushing Length:**

Between 0.781 inches and 0.843 inches

**Body Length:**

Between 0.735 inches and 0.765 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 3600.0 and 3610.0

**Maximum Starting Torque:**

0.80 inch-ounces

**Maximum Running Torque:**

0.80 inch-ounces

**Maximum Stop Torque:**

48.00 inch-ounces

**Shaft End Play:**

0.010 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

Ssn688foss

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.920 cubic inches

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.250/+0.250 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Unpackaged Unit Weight:**

0.75 ounces

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0