

View Online at <https://aerobasegroup.com/nsn/5905-01-306-9013>

Section Quantity:

1

Body Style:

Rectangular w/bushing/flange mounted

Reliability Indicator:

Not established

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

Between 0.984 inches and 1.016 inches

Mounting Bushing Length:

Between 0.234 inches and 0.266 inches

Body Length:

Between 0.468 inches and 0.500 inches

Body Width:

Between 0.608 inches and 0.640 inches

Body Height:

Between 0.734 inches and 0.766 inches

Shaft Style:

Round

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.296 inches and 0.328 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally closed

Fragility Factor:

Moderately rugged

End Application:

Fr-220a/u

Screw Thread Diameter:

Between 0.234 inches and 0.266 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Humidity proof and switch

Cubic Measure:

0.126 cubic inches

Electrical Resistance Per Section:

25.0 kilohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

3.000 ac

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0