NSN 5905-01-308-7826

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-308-7826

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsiu	s:

-25.0 to 25.0

Electrical Resistance:

4.340 kilohms

Resistance Tolerance In Percent:

-0.100 to 0.100

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 175.0

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

Between 1.000 inches and 1.625 inches

Body Diameter:

Between 0.085 inches and 0.165 inches

Body Length:

Between 0.260 inches and 0.437 inches

Power Dissipation Rating In Watts:

0.125 free air

End Application:

6625-01-016-5966 gain phase meter

Unpackaged Unit Weight:

0.45 grams

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-55182/3 government specification

Shelf Life:

N/a

NSN 5905-01-308-7826

Film Fixed Resistor - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A001a0