NSN 5905-01-308-7831

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-308-7831

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.110 inches
Shaft Length:
0.060 inches
Body Length:
0.750 inches
Body Width:
0.190 inches
Body Height:
0.270 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Fragility Factor:
Moderately rugged
End Application:
4920-01-141-0978 test stand, fuel pump
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Cubic Measure:
0.038 cubic inches
Electrical Resistance Per Section:
500.0 ohms c and better flooring
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 7th secondary quality
Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

NSN 5905-01-308-7831

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A002a0